



























NC スポットドリル ラインナップ

角度	ホルダー	インサート	D min.	D max.	モミツケ加工	面取り加工	V溝加工	刻印加工	センタードリル穴加工
60°	 99616-13V	 V9MT12T3	2	13	●	●	●	●	■
82°	 99619-V082-3/8	 V0820802	2	9	●	●	●	●	■
	 99619-V082-5/8	 V08212T3	2	14	●	●	●	●	■
90°	 99616-06-6	 N9MT05T1	1	6	●	●	●	●	■
	 99616-10...	 N9MT0802	2	10	●	●	●	●	■
	 99616-10-M5								
	 99616-14...	 N9MT11T3	3	14	●	●	●	●	■
	 99616-14-M8								
	 99616-22	 N9MT1704	3	22	●	●	●	●	■
	 99616-25-CT28	 N9MT220408	4	25	●	●	●	●	■
100°	 99616-20-100	 N9MT11T3CT2T-H	4	16	●	●	●	●	■
120°	 99616-20-120	 N9MT11T3CT2T-H	4	17	●	●	●	●	■
142°	 99616-20-142	 N9MT11T3CT2T-H	4	18.5	●	●	●	●	■
142°	 99619-V142	 V1421604	2	32	●	●	●	●	■